



AF Series Self Contained Flake Ice Machine – up to 150kg AF 156 AS OX Flake Ice



Flake ice



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Up to 150kg daily production rate
- 60kg storage bin capacity
- Air cooled version
- XSafe Natural Sanitation System
- Stainless steel auger and freezing cylinder evaporator
- Water in / ice out concept limits excess energy, water and time wastage
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- Simple, reliable electromechanic controls
- Clean alert indicator to clean filter
- Resistant stainless steel exterior
- Easy access front condenser air filter
- External indicator lights to show operation status
- Includes removable air filter, ice scoop, water and drain hose
























AF Series Self Contained Flake Ice Machine – up to 150kg

AF 156 AS OX









moffat.com.au

Australia Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

New South Wales

Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia

Telephone 03-9518 3888 vsales@moffat.com.au

Queensland


Telephone 07-3630 8600 qldsales@moffat.com.au

Western Australia

Telephone 08-9413 2400 wasales@moffat.com.au




AIR FLOW



UNIT OF MEASUREMENT: mm

- 1. 25/32" OVERFLOW DRAIN
- 2. 3/4" WATER INLET
- 3. 3/4" WATER OUTLET WATER COOLED UNIT ONLY
- 4. 3/4" WATER INLET WATER COOLED UNIT ONLY
- 5. CORD SET



Ice production per 24 hours

Ambient temperature / Water temperature

10°C / 10°C	21°C / 10°C	32°C / 21°C
160	150	118

Dimensions

Width: 950mm 605mm Depth:

1083mm (including legs) Height:

Nett weight: 75kg Packed weight: 88kg

Water consumption

Air cooled version: 5.2 litres per hour

Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 590W,

10A cordset supplied

No. Circuit wire: Compressor: 1570W Energy consumption: 13.8kW/24hr

Refrigerant type R404A

Installation distance from wall

Rear 150mm 150mm

Operating requirement air temperature 10-43°C

Water connection requirements

Inlet connection: R 3/4" 5-38°C Cold water: Pressure: 100-500kPa Water outlet connection: Ø3/4"

Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals



© Copyright Moffat Ltd

